

Uninterruptible Power Solution



MAGPRO – K SERIES



Extendible State of the Art UPS with Decentralize Bypass



UPS Cabinet Control Panel



Module Control Panel

Features

- High frequency and double conversion on-line technology
- Advanced PFC technology
- 3U frame, rack-mounted and tower convertible
- EPO function
- Wide input voltage range
- Fully digitized microprocessor control
- Parallel redundancy
- Advanced battery management
- Lightning and surge protection, short circuit and overload protection
- Multilingual LCD and LED display
- EMI/RFI noise filter
- Smart RS232 communication with monitoring software
- Optional SNMP card slot

single module(3U)



6kVA / 10kVA 1:1 phase
6kVA / 10kVA 3:1 phase

10kVA / 15kVA / 20kVA / 25kVA
/ 30kVA 3:3 phase

40kVA 3:3 phase



Battery Cabinets(Optional)



3 U Battery Box Optional



Technical Specifications:

MODEL		MPK1106-30KVA	MPK1110-50KVA	MPK3106-30KVA	MPK3110-50KVA	MPK3110-100KVA	MPK3320-60KVA	MPK3320-100KVA	MPK3320-200KVA	
Capacity (VA/watts)	UPS cabinet	6~30k / 4.8~24k	6~50k / 4.8~40k	6~30k / 4.8~24k	6~50k / 4.8~40k	6~100k / 4.8~80k	10~60k / 9~54k	10~100k / 9~90k	10~200k / 9~180k	
	MKP module	6k / 4.8k, 10k / 8k					10k / 9k, 15k / 13.5k, 20k / 18k			
INPUT										
Nominal voltage		220/230Vac		380/400Vac (3Ph+N+PE)or 220/230Vac			380/400/415Vac, (3Ph+N+PE)			
Operating voltage range		120~276Vac		208~478Vac or 120~276Vac			208~478Vac			
Operating frequency range		40~70Hz								
Power factor		≥0.99								
Bypass voltage range		Max.voltage: 220V +25%(optional +10%,+15%,+20%) 230V 20% (optional +10%,+15%) 240V 15%(optional +10%) Min. voltage: -45% (optional -20%,-30%) Frequency protection range: ± 10%								
Harmonic distortion (THDi)		5%(100% non-linear load)					2%(100% nonlinear load)			
Generator input		Support								
OUTPUT										
Output voltage		220/230Vac					380/400/415Vac, (3Ph+N+PE)			
Voltage regulation		± 1%								
Power factor		0.8					0.9/1 (Customized)			
Output frequency		1.Line Mode: ± 1%、± 2%、± 4%、± 5%、± 10% of the rated frequency (optional) 2.Battery Mode: (50/60 ± 0.1%)Hz								
Crest factor		3:1								
Harmonic distortion (THDv)		≤2% with linear load ≤5% with non linear load								
Efficiency		93.5%					95.5%			
BATTERY										
Battery voltage		± 96\ ± 108\ ± 120Vdc; battery quantity(optional)					± 192\ ± 204\ ± 216\ ± 228\ ± 240Vdc; battery quantity(optional)			
Charge Current	UPS cabinet	30A (Max.)	60A (Max.)	30A (Max.)		60A (Max.)	18A (Max.)	30A (Max.)	60A (Max.)	
	HPM module	6A (Max.) (charge current can be set according to battery capacity installed)								
Backup time		Depends on the capacity of external batteries								
SYSTEM FEATURES										
Transfer time		Utility to Battery : 0ms; Utility to bypass: 0ms								
Overload	Line Mode	Load ≤ 110%: last 60min, ≤ 125%: last 10min, ≤ 150%: last 1min, ≥ 150% turn to bypass mode immediately								
	Bat. Mode	Load ≤ 110%: last 30S, ≤ 125%: last 1S, ≤ 150%: last 200ms, ≥ 150% shut down UPS immediately					Load ≤ 110%: last 10min, ≤ 125%: last 1min, ≤ 150%: last 1S, ≥ 150% shut down UPS immediately			
	Bypass Mode	Breaker (6kVA:40A / 10kVA:60A)					Breaker (10kVA: 20A / 15kVA: 32A / 20kVA:40A)			
Short circuit		Hold whole system								
Noise suppression		Complies with EN62040-2								
Communication interface		1. UPS cabinet : RS232, RS485, Dry Contact, Intelligent slot x 2(SNMP card,Relay card optional) 2. HPM series UPS module: RS232								
ENVIRONMENTAL										
Operating temperature		0 ~ 40°C								
Storage temperature		-25 ~ 55°C								
Humidity range		0 ~ 95% (non condensing)								
Altitude		<1500m								
Noise level		<55dB					<65dB			
PHYSICAL										
Dimension D × W × H (mm)	UPS cabinet	840 × 600 × 1400	840 × 600 × 2000	840 × 600 × 1400		840 × 600 × 2000	840 × 600 × 1400		1100 × 600 × 2000	
	HPM module	443x580x131 (3U)								
Net weight (Kg)	UPS cabinet	138	150	138	150	213	149	152	290	
	HPM module	6kVA/23; 10kVA/25					10kVA/26; 15kVA/30; 20kVA/31			
STANDARDS										
Safety		IEC/EN62040-1,IEC/EN60950-1								
EMC		IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4, IEC61000-4-5,IEC61000-4-6,IEC61000-4-8								

Specifications are subject to change without prior notice.



Technical Specifications:

MODEL		MPK3325-250KVA	MPK3330-90KVA	MPK3330-150KVA	MPK3330-300KVA	MPK3340-400KVA	MPK3340-520KVA	MPK3340-800KVA	MPK3340-1040KVA	MPK3340-1060KVA	
Capacity (VA/watts)	UPS cabinet	250k / 225k	90k / 81k	150k / 135k	300k / 270k	400k / 360k	520k / 468k	800k / 720k	1040k / 936k	1560k / 1404k	
	MKP module	25k / 22.5k	25k / 22.5k, 30k / 27k			40k / 36k					
INPUT											
Nominal voltage		380/400/415Vac, (3Ph+N+PE)									
Operating voltage range		208~478Vac									
Operating frequency range		40~70Hz									
Power factor		≥0.99									
Bypass voltage range		Max.voltage: 220V +25%(optional +10%,+15%,+20%) 230V 20% (optional +10%,+15%) 240V 15%(optional +10%) Min. voltage: -45% (optional -20%,-30%) Frequency protection range: ± 10%									
Harmonic distortion (THDi)		3%(100% nonlinear load)									
Generator input		Support									
OUTPUT											
Output voltage		380/400/415Vac, (3Ph+N+PE)									
Voltage regulation		± 1%									
Power factor		0.9									
Output frequency		1.Line Mode: ± 1%、± 2%、± 4%、± 5%、± 10% of the rated frequency (optional) 2.Battery Mode: (50/60± 0.1%)Hz									
Crest factor		3:1									
Harmonic distortion (THDv)		≤2% with linear load ≤5% with non linear load									
Efficiency		95.0%									
BATTERY											
Battery voltage		± 192\ ± 204\ ± 216\ ± 228\ ± 240Vdc; battery quantity(optional)									
Charge Current	UPS cabinet	60A (Max.)	30A(Max.)	50A(Max.)	100A(Max.)	130A (Max.)	200A (Max.)	260A (Max.)	390A (Max.)		
	HPM module	6A (Max.)	25kVA:6A (Max.) / 30kVA:10A (Max.)			10A (Max.)					
Backup time		Depends on the capacity of external batteries									
SYSTEM FEATURES											
Transfer time		Utility to Battery : 0ms; Utility to bypass: 0ms									
Overload	Line Mode	Load ≤ 110%: last 60min, ≤ 125%: last 10min, ≤ 150%: last 1min, ≥ 150% turn to bypass mode immediately									
	Bat. Mode	Load ≤ 110%: last 10min, ≤ 125%: last 1min, ≤ 150%: last 1s, ≥ 150% shut down UPS immediately					Load ≤ 110%: last 60min, ≤ 125%: last 10min, ≤ 150%: last 1min, ≥ 150% shut down UPS immediately				
	Bypass Mode	Breaker (25kVA:40A)	Breaker (25kVA:40A / 30kVA:60A)			40kVA:95A					
Short circuit		Hold whole system									
Noise suppression		Complies with EN62040-2									
Communication interface		1. UPS cabinet : RS232, RS485, Dry Contact, Intelligent slot x 2(SNMP card,Relay card optional) 2. HPM series UPS module: RS232									
ENVIRONMENTAL											
Operating temperature		0 ~ 40°C									
Storage temperature		-25 ~ 55°C									
Humidity range		0 ~ 95% (non condensing)									
Altitude		<1500m									
Noise level		<70dB					<73dB				
PHYSICAL											
Dimension D × W × H (mm)	UPS cabinet	600 × 1100 × 2000	600 × 840 × 1400		600 × 1100 × 2000	1200 × 860 × 2000	1800 × 860 × 2000	3000 × 860 × 2000	4800 × 1100 × 2000		
	HPM module	443x580x131 (3U)									
Net weight (Kg)	UPS cabinet	290	158	170	307	750	860	1300	1810	2800	
	HPM module	32	25kVA/32; 30kVA/33.5			34					
STANDARDS											
Safety		IEC/EN62040-1,IEC/EN60950-1									
EMC		IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4, IEC61000-4-5,IEC61000-4-6,IEC61000-4-8									

Specifications are subject to change without prior notice.



BizPark Commercial Estate Blok A3/3
Jalan Raya Bekasi Km. 21.5, Rawa Terate
Cakung, Jakarta Timur 13920, Indonesia
Tel: + 62 21 4682 7000
Fax: + 62 21 4682 9200
Website: www.ups4.com